In the claims:

Please amend the claims as follows:

- 1. (cancelled)
- 2. (cancelled)
- 3. (cancelled)
- 4. (cancelled)
- 5. (cancelled)
- 6. (currently amended) A kit for attachment between a door and a wall, said door moveable between an open position in which an end of said door is spaced from said wall, an ajar position, and a closed position, said door having a door latch with a retractable latch bolt for engaging a latch plate on said wall, said bolt retractable by rotating a handle, said kit for unlatching said door latch and said kit for urging said door between said closed position and said open position, said kit comprising

a connector attachable to one of said door and said wall,

moveable means attachable to the other of said door and said wall, said moveable means driven by a first <u>electric</u> motor,

said moveable means for applying force to said door for moving said door from said ajar position to said closed position and for applying force to said door for moving said door from said closed position to said ajar position,

said moveable means spaced from said connector when said door is in said open position and engaged with said connector when said door is in said ajar position and said closed position,

a door operator having a linkage attachable between said door and said wall, said door operator for moving said door from said ajar position to said open position, said door operator driven by a <u>electric</u> second motor, and an unlatching device attachable to said door and said handle, said unlatching device to rotating said handle and retracting said bolt.

said unlatching device not requiring attachment to said wall,
said unlatching device operated by a third electric motor,

electronic means for controlling said first motor and said second motor and said third motor for coordinating the unlatching of said door with said moveable means and said door operator for providing unified movement of said door between said closed and latched position and said open position, and-

a power source integral with one of a said unlatching device, said door operator and said moveable means for providing power to said parts.

7. (cancelled)

8. (withdrawn) The method of controlling the opening of a door in a wall, said door moveable between a n open position, and a closed position, and having an ajar position between said open and said closed position, said door having a latch with a retractable bolt for engaging a latch plate on said wall, said bolt retracted by rotating a handle on said latch, said method comprising the steps of,

providing a door operating device attachable to said door and said wall, said door operating device for moving said door from said closed position to said open position,

attaching said door operating device to said door and said wall,

providing an unlatching device attachable to said door and said handle for rotating said handle to unlatch said door,

attaching said unlatching device to said door and said handle,

providing means for coordinating the operators of said unlatching device and said door operating device wherein said unlatching device will unlatch a closed door after which said door operating device will open said door.

9. (withdrawn) The method of claim 8 wherein said door operating device also moves said door from said open position to said closed position and said means for coordinating the operations of said unlatching device and said door operating device will carry out the steps of

said unlatching device rotating said handle to retract said latch bolt while said door is in said open position,

said door operating device moving said door from said open position to said closed position,

said unlatching device releasing said handle to extend said bolt into said latch plate,

said door operating device holding said door in said closed position until said unlatching device has released said handle to extend said bolt, and

terminating power to said door operating device after said unlatching device has released said handle to extend said bolt.

10. (withdrawn) The method of claim 8 and comprising the further steps of providing an assist attachable to said door and said wall, said assist for applying additional force to move said door between said closed position and said ajar position,

attaching said assist to said door and said wall, and

providing said means for coordinating where said means for coordinating coordinates the operations of said unlatching device, said door operating and said assist wherein said unlatching device, said door operating and said assist wherein said unlatching device will unlatch a closed door after which said assist will urge said door from said closed position to said ajar position and said door operating device will open said door.